



DOUBLE DISC 1300

Spreaders


Discover why the JF Double Disc 1300 and JF Double Disc 1300 FR spreaders are perfect solutions for covering your land with productivity.

FEATURES

- ✓ Working width from 16 to 36m;
- ✓ Discs with 4 paddles with adjustable positions for uniform distribution;
- ✓ Discs, paddles, gates, and bottom closure made of stainless steel for greater strength and durability;
- ✓ Simple adjustment dosing for greater agility in operation;
- ✓ Tank made of high-resistance UV-protected polyethylene;
- ✓ Special agitator (optional) for working with limestone;
- ✓ Excellent cost-benefit ratio, combining precision and durability at a low maintenance cost.



Distribution system:
Stainless steel



Fixed rate version:
Automatic distribution



Protection grid:
Agitator with smoother flow

FIXED RATE

New version JF Double Disc 1300

The fixed-rate application technology ensures that distribution remains uniform, regardless of the tractor's speed.

TECHNICAL SPECS

⏻ Power source	Tractor PTO	↔ Working width (range)	16 up to 36m
📊 Capacity	1300 liters	🔄 Required rotation at PTO	540 RPM
↑↓ Height	1300mm	⚡ Required power at PTO	30 hp
↔ Width	2350mm	📦 Approx. weight	274 kg